

### Reduction gear 1 450 rpm

Option : Steel hose reel



#### MAIN FEATURES

- ▶ Pump + reduction gear : longer lifetime
- ▶ Anti water hammer regulator
- ▶ Solid frame



#### OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension
- ▶ 4 - Sanding kit
- ▶ 5 - Wheelbarrow arms
- ▶ 6 - Hydro-ejector
- ▶ 7 - Drain cleaning kits

### ● SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Reduction gear : reduces the pump rotation speed
- Petrol engine with lack of oil safety
- Pull start
- Welded steel frame and hood, epoxy paint

### ● STANDARD EQUIPMENT

- Hose : 10 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- Lance : 900 mm double lance adjustable high & low pressure
- Quick coupling : on the outlet of the pump
- Pneumatic wheels : Ø 500 mm

### ● MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT
	l/min	l/h		Motor	HP	rpm	Brand	Oil	
TIE 21 180 H	21	1260	180	HONDA	13	1 450	INTERPUMP	15W40	81