

NETTOYEURS ESSENCE

Intensive, high flow rate - Ref. : JTE 22 250 HDE



V-belt drive
1450 rpm

2026
Selection



MAIN FEATURES

- ▶ Long-life pump
- ▶ Anti water hammer regulator
- ▶ V-belt drive
- ▶ Less vibrations
- ▶ Better output
- ▶ Quieter
- ▶ Anti-fatigue spray gun



OPTIONS

- ▶ 1 - Sanding kit
- ▶ 2 - Hose extension
- ▶ 3 - Hydro-ejector kit
- ▶ 4 - Drain cleaning kit

SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- Petrol engine with lack of oil safety
- V-belt drive : Flexible transmission of power
- Frame and carter : welded steel, epoxy paint



SELECTION EQUIPMENT

- HP hose : 20 m 3/8 double metal braided hose
- Anti-fatigue HP gun : with swivel link (on hose side)
- Lance : stainless steel 1050 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Pneumatic wheels : Ø 600 mm

Use :



Semi-pro Professional Intensive Super Intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		START	POIDS	DIMENSIONS
	l/min	l/h	bar	Engine	HP	rpm	Brand	Huile		kg	cm (L x l x h)
JTE 22 250 HDE	22	1320	250	HONDA	21 Bi-cylinder	1450	INTERPUMP	15W40	Electric	146	125 x 83 x 70

