

# THREE PHASE HP WASHERS

## Standard series - Ref. FP 15 200



**Direct drive**  
1 450 rpm



### MAIN FEATURES

- ▶ High quality crankshaft pump
- ▶ Thermal safety valve
- ▶ Lance holders
- ▶ Wheelbarrow arms



### OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Time delayed total stop
- ▶ 3 - Turbo lance
- ▶ 4 - Hose extension

### SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Integrated detergent application system
- Three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel frame epoxy paint
- ABS hood

### STANDARD EQUIPMENT

- Hose : 10 m 5/16 single metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm single lance: with adjustable head & flat jet nozzle
- Rubber-tyred wheels : Ø 260 mm

### MODELS



REFERENCE	FLOW RATE		PRESSURE bar	POWER		rpm	PUMP		WEIGHT kg
	l/min	l/h		HP	KW		Brand	Oil	
FP 15 200	15	900	200	7,5	5,6	1 450	BERTOLINI	80W90	70

ELECTRIC

