

THREE PHASE HP WASHERS

Intensive series 7.5 HP - Ref. IP 21 150




Flector coupling
1 450 rpm

2026
Selection



MAIN FEATURES

- ▶ Long life pump
- ▶ Thermal safety valve
- ▶ Elastic coupling
- ▶ Lance holders
- ▶ Wheelbarrow arms



● SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Integrated detergent application system
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : Three phase electric engine
- Magneto-thermal circuit breaker
- 5 m electric cable
- Welded steel frame, epoxy paint
- ABS hood

● SELECTION EQUIPMENT

- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Rubber-tyred wheels : Ø 260 mm

OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Time delayed total stop
- ▶ 3 - Hose extension
- ▶ 4 - Sanding kit

● MODEL

Use :



REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	KW	rpm	Brand	Oil	kg	cm (L x l x h)
IP 21 150	21	1 260	150	7,5	5,6	1 450	INTERPUMP	15W40	81	140 x 62 x 77

