

# THREE PHASE HP WASHERS

## Intensive series 12 HP - Ref. IP 30 170




### Flector coupling

1 450 rpm



#### MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Pneumatic wheels
- ▶ Lance holders
- ▶ Wheelbarrow arms



### SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel frame, epoxy paint
- ABS hood

### STANDARD EQUIPMENT

- Hose : 10 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 1050 mm double lance adjustable high & low pressure
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm

### MODELS

#### OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Time delayed total stop
- ▶ 3 - Turbo lance
- ▶ 4 - Hose extension
- ▶ 5 - Sanding kit



Use :



Semi-pro Professional Intensive Super Intensive

REFERENCE	FLOW RATE		PRESSURE	POWER		rpm	PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW		Brand	Oil	kg	cm (L x l x h)
IP 30 170	30	1 800	170	12	9,2	1 450	INTERPUMP	15W40	115	146 x 70 x 73

