

Flector coupling - 1 450 rpm




Mobile version



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Equipment ensuring great work comfort



OPTIONS

- ▶ 1 - Star delta starter box
- ▶ 2 - Hose extension

SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric 20 HP engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : welded steel

Stationary unit

STANDARD VHP EQUIPMENT

- Hose : 20 m 3/8 double metal braided
- HP spray gun with stainless steel half lance : with swivel link (on hose side)
- 400 mm stainless steel lance : with 25° HP nozzle
- 400 mm stainless steel lance : with turbo nozzle

MODEL



REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		Stationary unit with 100 L buffer tank
	l/min	l/h		HP	kW	rpm	Brand	Oil	
SIP 21 350 T	21	1 260	350	20	15	1 450	UDOR	15W40	SIP 21 350 TF

Check our recommended very high pressure personal protective equipment

