


Flector coupling - 1 450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Equipment ensuring great work comfort



OPTIONS

- ▶ 1 - Star delta starter box
- ▶ 2 - Hose extension

SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold with pressure drop to zero
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric 20 HP engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel

STANDARD VHP EQUIPMENT

- Hose : 20 m 3/8 double metal braided
- HP spray gun with stainless steel half lance : with swivel link (on hose side)
- 400 mm stainless steel lance : with 25° HP nozzle
- 400 mm stainless steel lance : with turbo nozzle

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP		
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil
SIP 15 500 T	15	900	500	20	15	1 450	INTERPUMP	15W40

Check our recommended very high pressure personal protective equipment