

# THREE PHASE HP WASHERS

Stationary unit - Ref. : SIP 26 150 TF




## Flector coupling

1 450 rpm



### MAIN FEATURES

- ▶ Long life pump
- ▶ Elastic coupling



### SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel board
- ABS hood

### OPTIONS

- ▶ 1 - Turbo lance
- ▶ 2 - Hose extension
- ▶ 3 - Double foam kit

### STANDARD EQUIPMENT

- Frame : welded steel
- Buffer tank : 100 litres
- Hose : 10 m 3/8 double metal braided hose
- HP spray gun : with swivel link (on hose side)
- 1050 mm double lance : adjustable high & low pressure
- Quick coupling on the outlet of the pump

Use :



Semi-pro Professional Intensive Super Intensive

### MODEL

REFERENCE	WATER FLOW		PRESSURE bar	POWER		rpm	PUMP		POIDS kg
	l/min	l/h		HP	kW		Brand	Oil	
SIP 26 150 TF	26	1560	150	10	7,5	1450	INTERPUMP	15W40	108

