

# THREE PHASE HP WASHERS

Stationary unit - Ref. : SIP 30 170 TF



**Flector coupling**  
1 450 rpm

2026  
Selection



**INTERPUMP GROUP**

## MAIN FEATURES

- ▶ Long life pump
- ▶ Elastic coupling



ELECTRIC

## SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel board
- ABS hood

## SELECTION EQUIPMENT

- Frame : welded steel
- Buffer tank : 100 litres
- Hose : 20 m 3/8 double metal braided hose
- HP spray gun : with swivel link (on hose side)
- 1050 mm double lance : adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling on the outlet of the pump

## MODEL

Use :

Semi-pro Professional Intensive Super Intensive

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP	WEIGHT	DIMENSIONS		
	l/min	l/h		HP	kW				rpm	Brand
SIP 30 170 TF	30	1800	170	12	9,2	1450	INTERPUMP	15W40	175	95 x 65 x 150

