

# HOT WATER HP WASHERS

Three-phase - Standard series - FP 15 200 HW



**Direct drive**  
1 450 rpm



## MAIN FEATURES

- ▶ Lack of fuel safety
- ▶ Lack of water safety
- ▶ Shutdown on micro leak
- ▶ 24 V total stop



## OPTIONS

- ▶ 1 - ABS hose reel (max 20 m)
- ▶ 2 - Double foam kit
- ▶ 3 - Antiscale kit (preventive & curative)

## SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Engine : Three phase electric engine
- Thermal circuit breaker
- Frame and hood : welded stainless steel
- Electric cable : 5 m
- Boiler : High efficiency vertical stainless steel boiler, steel coil
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 24 l

## STANDARD EQUIPMENT

- Blue hose : 10 m 5/16 double metal braided hose
- HP spray gun : with link
- 900 mm lance with adjustable head and flat jet nozzle



## MODELS

| REFERENCE    | FLOW RATE |     | PRESSURE | POWER |     | PUMP |           |       | TEMPERATURE | WEIGHT |
|--------------|-----------|-----|----------|-------|-----|------|-----------|-------|-------------|--------|
|              | l/min     | l/h | bar      | HP    | kW  | rpm  | Brand     | Oil   | °C          | kg     |
| FP 15 200 HW | 15        | 900 | 200      | 7,5   | 5,5 | 1450 | INTERPUMP | 15W40 | 65/140      | 182    |

