

HOT WATER HP WASHERS

Three-phase - Standard series - FP 14 150 HW



Direct drive
1 450 rpm



MAIN FEATURES

- ▶ Lack of fuel safety
- ▶ Lack of water safety
- ▶ Shutdown on micro leak
- ▶ 24 V total stop



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Engine : Three phase electric engine
- Thermal circuit breaker
- Frame and hood : welded stainless steel
- Electric cable : 5 m
- Boiler : High efficiency vertical stainless steel boiler, steel coil
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 24 l

STANDARD EQUIPMENT

- Blue hose : 10 m 5/16 double metal braided hose
- HP spray gun : with link
- 900 mm lance with adjustable head and flat jet nozzle

OPTIONS

- ▶ 1 - ABS hose reel (max 20 m)
- ▶ 2 - Double foam kit
- ▶ 3 - Antiscale kit (preventive & curative)



MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			TEMPERATURE	WEIGHT
	l/min	l/h		HP	kW	rpm	Brand	Oil		
FP 14 150 HW	14	840	150	5,5	4,5	1 450	INTERPUMP	15W40	65/140	145

