

HOT WATER HP WASHERS

Three-phase - Intensive series - I 21 150 HW




Flector coupling
1 450 rpm



MAIN FEATURES

- ▶ Lack of fuel safety
- ▶ Lack of water safety
- ▶ 24 V total stop



OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Double foam kit
- ▶ 3 - Antiscale kit (preventive & curative)



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Engine : Three phase electric engine
- Engine safety
- Flector coupling : increased elasticity of the motor-pump coupling
- Steel frame, epoxy paint
- Hood : autoextinguishable ABS
- Electric cable : 5,5 m
- High efficiency vertical boiler, with refractory cement base
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 22 l
- Anti scale device with poly-phosphate crystals
- Detergent tank capacity : 20 l
- Automatic stop system : 60 minutes after releasing the trigger
- Total stop : in case of micro leak
- Possibility to work with steam

STANDARD EQUIPMENT

- Blue hose : 10 m 3/8 double metal braided hose
- HP spray gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Rubber-tyred wheels : Ø 300 mm
- Swivel castor : with break

MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			TEMPERATURE	WEIGHT
	l/min	l/h		HP	kW	rpm	Brand	Oil		
I 21 150 HW	21	1260	150	8	6	1450	INTERPUMP	15W40	65/140	219

