

Transmission réductée 1 450 tr/min



MAIN FEATURES

- ▶ Pompe + réducteur : longue durée de vie
- ▶ Anti water hammer regulator
- ▶ Easy access to motor & pump components



HP WASHER SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- **Reduction gear** : reduces the pump rotation speed
- **Engine** : petrol engine with lack of oil safety or Diesel depending on model
- **Electric or pull start** depending on model
- **Board** : mounted on silentblocs
- **Board and hood** : welded steel, epoxy paint



OPTIONS

- ▶ 1 - Antifreeze kit (22 l tank)
- ▶ 2 - Detergent kit
- ▶ 3 - Sanding kit
- ▶ 4 - Suction kit

TRAILER SPECIFICATIONS

- Trailer with one braked axle
- Manual jockey wheel
- Supporting frame : galvanized steel
- **Anti-rolling water tank** : 1100 L
- **Water filter** : 50 µ

STANDARD EQUIPMENT

- Manual steel HP hose reel
- Hose :
 - REM TIE 41 150 HDE : 30 m 3/8 double metal braided
 - Other models : 20 m 3/8 double metal braided
- HP spray gun : with swivel link (on hose side)
- Lance : 900 mm double lance adjustable high & low pressure
- 700 mm turbo lance
- 2 unblocker nozzles : for REM TIE 41 150 HDE only

MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER				PUMP		
	l/min	l/h		bar	Motor	Fuel	CV	Start	tr/min	Marque
REM TIE 18 240 HE	18	1100	240	HONDA	Petrol	13	Pull	1450	INTERPUMP	15W40
REM TIE 41 150 HDE	41	2 460	150	HONDA	Petrol	24 bi-cylinder	Electric	1450	INTERPUMP	15W40
REM TID 15 200 YDE	15	900	200	YANMAR	Diesel	10	Electric	1450	INTERPUMP	15W40

Please check that you have the necessary driving licence referring to local legislation.