

DIESEL HP WASHERS

Intensive series - Ref TID 15 200 YD



Reduction gear
1 450 rpm

2026
Selection



MAIN FEATURES

- ▶ Pump + reduction gear : longer lifetime
- ▶ Anti water hammer regulator
- ▶ Solid frame



COMBUSTION ENGINE

SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Reducer : reduces the rotation speed of the pump
- Diesel engine
- Electric start
- Welded steel frame and hood, epoxy paint



OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Sanding kit
- ▶ 4 - Hydro-ejector kit
- ▶ 5 - Drain cleaning kits

SELECTION EQUIPMENT

- HP hose : 20 m 3/8 double metal braided hose
- HP spray gun : with swivel link (on hose side)
- Lance : 900 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling : on the outlet of the pump
- Pneumatic wheels : Ø 500 mm

Use :



Semi-pro Professional Intensive Super Intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	Engine	HP	rpm	Brand	Oil	kg	cm (Lx l x h)
TID 15 200 YD	15	900	200	YANMAR	10	1 450	INTERPUMP	15W40	120	105 x 70 x 75

