PETROL HP WASHERS

Standard series - Ref: TSL 15 240 HEPA





PCTION MAIN FEATURES

- Thermal safety valve
- ► High quality crankshaft pump
- Anti water hammer regulator









SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Pump safety: VST (thermal safety valve)
- Regulator: separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Petrol engine with lack of oil safety
- Petrol engine with RPM automatic regulator
- Pull start
- Welded steel frame and hood, epoxy paint

паса зсестнате ана поод, ероху ранк

What is the RPM automatic regulator $\ref{eq:constraint}$

The RPM regulator is a system that automatically slows down the engine of the HP washer when it is working in closed circuit (trigger of the spray gun released).

• STANDARD EQUIPMENT SELECTION 2022

- Hose reel: ABS on reinforced hood
- Hose: 20 m 3/8 double metal braided hose
- **HP gun**: with swivel link (on hose side)
- Lance: 900 mm adjustable high & low pressure double lance
- Lance: 700 mm with turbo nozzle OFFERED ITEM
- Quick coupling: on the outlet of the pump
- Pneumatic wheels : Ø 400 mm

OPTIONS

- ▶ 1 ABS or steel hose reel
- ▶ 2 Hose extension
- ▶ 3 Sanding kit

Use:



Semi-pro Professional Intensive Super Intensive



Reduction of the petrol consumption: 1.2 l

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			WEIGHT
	Vmin	l/h	bar	Motor	HP	rpm	Brand	Oil	kg
TSL 15 240 HEPA	15	900	240	HONDA GX	13	3 400	BERTOLINI	80W90	67