

PETROL HP WASHERS

Standard series - Ref. : TSL 15 240 HEPA



Direct drive
3 400 rpm

2026
Selection



MAIN FEATURES

- ▶ Thermal safety valve
- ▶ High quality crankshaft pump
- ▶ Anti water hammer regulator



SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Petrol engine with lack of oil safety
- Pull start
- Welded steel frame and hood, epoxy paint



OPTIONS

- ▶ 1 - Hose extension
- ▶ 2 - Sanding kit

What is the RPM automatic regulator ?

The RPM regulator is a system that automatically slows down the engine of the HP washer when it is working in closed circuit (trigger of the spray gun released).

SELECTION EQUIPMENT

- Hose reel : ABS on reinforced hood
- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- Lance : 900 mm adjustable high & low pressure double lance
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling : on the outlet of the pump
- Pneumatic wheels : Ø 400 mm



Use :



MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	Engine	HP	rpm	Brand	Oil	kg	cm (L x l x h)
TSL 15 240 HEPA	15	900	240	HONDA GX	13	3 400	BERTOLINI	80W90	77	105 x 59 x 80

