

DIESEL HP WASHERS

Standard series - Ref. : TSD 15 200 Y



Direct drive
3 400 rpm

2026
Selection



MAIN FEATURES

- ▶ Quality crankshaft pump
- ▶ High quality crankshaft pump
- ▶ Anti water hammer regulator



OPTIONS

- ▶ 1 - ABS or steel hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Sanding kit

SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Diesel engine
- Pull start
- Welded steel frame and hood, epoxy paint



SELECTION EQUIPMENT

- Hose : 10 m 5/16 single metal braided hose
- HP spray gun : with swivel link (on hose side)
- Lance : 900 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling : on the outlet of the pump
- Pneumatic wheels : Ø 500 mm

Use :



Semi-pro Professional Intensive Super Intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	Engine	HP	rpm	Brand	Oil	kg	cm (Lx l x h)
TSD 15 200 Y	15	900	200	YANMAR	10	3 400	BERTOLINI	80W90	84	105 x 70 x 75

