

HOT WATER HP WASHER

Three phase - Standard use - Ref. : DIMACTION 14 160 HW



Direct drive
1450 rpm

2026
Selection



MAIN FEATURES

- ▶ Time delayed total stop
- ▶ Easy to handle
- ▶ Lance holder



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : automatic shutdown of engine managed by spray gun
- Regulator : separated from the manifold
- Three phase electric engine
- Detergent application system : integrated
- Electric cord : 5 m
- Boiler : steel construction
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 16 l
- Wheels : 2 Rubber-tyred wheels 1 castor wheel
- Frame : Steel/polypropylene
- Hood : ABS



OPTIONS

- ▶ 1 - Hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Antiscale kit (curative)
- ▶ 4 - Turbo lance

STANDARD EQUIPMENT

- Blue hose : 10 m 5/16 double metal braided
- HP spray gun : with link
- 900 mm double lance adjustable high & low pressure



A TOTAL STOP, WHAT IS IT?

Standby system on the high-pressure washer

Use :



Semi-pro Professional Intensive Super intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			TEMPERATURE	WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil	°C	kg	cm (L x l x h)
DIMACTION 14 160 HW	14	840	160	5,5	4,1	1450	ANNOVI	15W40	65/140	92	80 x 58 x 90



SAT DIMACO Constructeur, ZI, 15 rue Gustave Eiffel, 37500 CHINON (France) - Tél. + 33 (0)2 47 98 25 36

E-mail : export@dimaco.com - Site Internet : www.dimaco.com

V1 - vm

HOT WATER