

HOT WATER HP WASHERS

Three-phase - Professional series



Direct drive
1 450 rpm



MAIN FEATURES

- ▶ Lack of fuel safety
- ▶ Lack of flame safety
- ▶ Antiscale device
- ▶ Lack of use function : stops the machine after 20 minutes of inactivity



OPTIONS

- ▶ 1 - ABS hose reel
- ▶ 2 - Double foam kit
- ▶ 3 - Antiscale kit (preventive & curative)

SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : Automatic engine stop when trigger of the gun is released
- Regulator : Separated from the manifold
- Engine : Three phase electric engine
- Thermal circuit breaker
- Integrated detergent application system
- Detergent tank capacity : 20 l
- Electric cable : 5 m
- Boiler : stainless steel boiler, steel coil
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 35 l
- Frame : Steel and polypropylene
- Hood : stainless steel
- Front bumper

STANDARD EQUIPMENT

- Blue hose : 10 m 5/16 double metal braided hose
- HP spray gun : with link
- 900 mm lance with adjustable head and flat jet nozzle
- Rubber-tyred wheels
- 2 Swivel castors : with break

Use :



Semi-pro Professional Intensive Super intensive

MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP		TEMPERATURE	WEIGHT
	l/min	l/h		HP	kW	rpm	Brand		
FP 15 200 HW PREMIUM	15	900	200	7.5	5.5	1 450	INTERPUMP	65/140	148

