THREE PHASE HP WASHERS

Very high pressure - Intensive - *Ref. : IG 15 500*

DIMACO

Flector coupling
1 450 rpm

2026 Selection

INTERPUMP GROUP

MAIN FEATURES

- Long life pump
- Elastic coupling
- Pneumatic wheels
- Equipment ensuring great work confort

400 V

Flector

WARRANTY 2 YEARS

ELECTRIC

OPTIONS

- 1 - Hose extension

SPECIFICATIONS

- **Crankshaft pump** (radial), 3 ceramic pistons
- **Pump safety :** VST (thermal safety valve)
- **Regulator :** separated from the manifold with pressure drop to zero
- **Flector coupling :** increased elasticity of the motor-pump coupling
- **Engine :** three phase electric 20 HP engine
- Magneto-thermal **circuit breaker**
- **Electric cable :** 5 m
- **Frame and hood :** galvanized welded steel

SELECTION VHP EQUIPMENT

- **Hose :** 20 m 3/8 double metal braided
- **HP spray gun with stainless steel half lance :** with swivel link (on hose side)
- **400 mm stainless steel lance :** with 25° HP nozzle
- **400 mm stainless steel lance : with turbo nozzle**
- **Rubber-tyred wheels :** Ø 400 mm

Use :

Semi-pro | Professional | Intensive | Super Intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil	kg	cm (Lx l x h)
IG 15 500	15	900	500	20	15	1 450	INTERPUMP	15W40	168	131 x 77 x 79

DIMACO

SAT DIMACO Constructeur, ZI, 15 rue Gustave Eiffel, 37500 CHINON (France) - Tél. + 33 (0)2 47 98 25 36
E-mail : export@dimaco.com - Site Internet : www.dimaco.com