

# THREE PHASE HP WASHERS

Very high pressure - Intensive - Ref. : IG 15 500 F



## Flector coupling 1 450 tr/min



### MAIN FEATURES

- ▶ Long life pump
- ▶ Elastic coupling



400 V

Flector



WARRANTY

2  
YEARS

ELECTRIC

## SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric 20 HP engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel frame, epoxy paint
- Hood : galvanized welded steel
- 100 l buffer tank

### OPTIONS

- ▶ 1 - Hose extension

## STANDARD VHP EQUIPMENT

- Hose : 20 m 3/8 double metal braided
- HP spray gun with stainless steel half lance : with swivel link (on hose side)
- 400 mm stainless steel lance : with 25° HP nozzle
- 400 mm stainless steel lance : with turbo nozzle

Use :



Semi-pro Professional Intensive Super Intensive

## MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil	kg	cm (L x l x h)
IG 15 500 F	15	900	500	20	15	1 450	INTERPUMP	15W40	185	88 x 55 x 147

Check our recommended very high pressure personal protective equipment

