

THREE PHASE HP WASHERS

Intensive series - Stainless steel - Agro industry



Flector coupling 1 450 rpm




INTERPUMP
GROUP



Hot water admissible

MAIN FEATURES

- ▶ Long life pump
- ▶ Total stop
- ▶ Elastic coupling
- ▶ Water input temperature up to 71° C



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 10 m
- Frame and hood : stainless steel folded metal sheet

STANDARD EQUIPMENT

- Hose reel : stainless steel
- Hose : 25 m 3/8 blue double metal braided hose
- HP spray gun : with swivel link (on hose side)
- 700 mm single lance with flat jet nozzle
- Quick coupling on the outlet of the pump
- Wheels : 2 swivel castor wheels

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			WEIGHT
	l/min	l/h		HP	KW	rpm	Brand	Oil	
NAGRO120/20IP	20	1200	120	5.5	4	1450	INTERPUMP	15W40	122

OPTIONS

- ▶ 1 - Lack of water (low pressure) safety
- ▶ 2 - Buffer tank + temperature regulation



ELECTRIC

