

THREE PHASE HP WASHERS

Intensive series 7.5 HP - Ref. IP 15 200 ST



Flector coupling
1 450 rpm

2026
Selection



MAIN FEATURES

- ▶ Long life pump
- ▶ Elastic coupling
- ▶ Lance holders
- ▶ Wheelbarrow arms



● SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- **Total stop** : Automatic Start/Stop system managed by the spray gun
- **Regulator** : separated from the manifold
- Integrated **detergent application system**
- **Flector coupling** : increased elasticity of the motor-pump coupling
- **Engine** : Three phase electric engine
- Magneto-thermal **circuit breaker**
- 5 m electric cable
- **Welded steel frame**, epoxy paint
- **ABS hood**



OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Sanding kit



A TOTAL STOP, WHAT IS IT?

Standby system on the high-pressure washer

● SELECTION EQUIPMENT

- **Hose** : 20 m 3/8 double metal braided hose
- **HP gun** : with swivel link (on hose side)
- **900 mm double lance** adjustable high & low pressure
- **Lance** : 700 mm with turbo nozzle **FOR FREE**
- **Rubber-tyred wheels** : Ø 260 mm

Use :



Semi-pro Professional Intensive Super intensive

● MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	KW	rpm	Brand	Oil	kg	cm (L x l x h)
IP 15 200 ST	15	900	200	7,5	5,6	1450	INTERPUMP	15W40	81	140 x 62 x 77

