

THREE PHASE HP WASHERS

Intensive series - Galvanized - Ref. : IG 26 150 ST



Flector coupling
1 450 rpm

2026
Selection



- MAIN FEATURES**
- ▶ Long life pump
 - ▶ Anti water hammer regulator
 - ▶ Elastic coupling
 - ▶ Pneumatic wheels
 - ▶ Lance holders
 - ▶ Wheelbarrow arms



ELECTRIC

SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : Automatic Start/Stop system managed by the spray gun
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel



- OPTIONS**
- ▶ 1 - Steel hose reel
 - ▶ 2 - Turbo lance
 - ▶ 3 - Hose extension
 - ▶ 4 - Sanding kit

SELECTION EQUIPMENT

- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm

STT A TOTAL STOP, WHAT IS IT?
Standby system on the high-pressure washer

Use :



Semi-pro Professional Intensive Super Intensive

MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP	WEIGHT	DIMENSIONS		
	l/min	l/h		bar	HP				kW	rpm
IG 26 150 ST	26	1560	150	12	9,2	1450	INTERPUMP	15W40	123	131 x 77 x 79

