

THREE PHASE HP WASHERS

Intensive series - Galvanized - Ref. : IG 30 170 ST



Flector coupling
1 450 rpm

2026
Selection



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Pneumatic wheels
- ▶ Lance holders
- ▶ Wheelbarrow arms



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : Automatic Start/Stop system managed by the spray gun
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel



OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension
- ▶ 4 - Sanding kit

SELECTION EQUIPMENT

- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Lance : 700 mm with turbo nozzle **FOR FREE**
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm



A TOTAL STOP, WHAT IS IT?

Standby system on the high-pressure washer

Use :



Semi-pro Professional Intensive Super Intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			WEIGHT	DIMENSIONS
	l/min	l/h		HP	kW	rpm	Brand	Oil		
IG 30 170 ST	30	1800	170	12	9,2	1450	INTERPUMP	15W40	123	131 x 77 x 79

