

THREE PHASE HP WASHERS

Stand-alone unit - Ref. : SM 26 90



Flector coupling

1 450 tr/min



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Galvanized board



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Integrated detergent application system
- Three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Galvanized welded steel board
- ABS hood

STANDARD EQUIPMENT

- Hose : 10 m 5/16 single metal braided hose
- HP spray gun : with swivel link (on hose side)
- Single lance with adjustable head & flat jet nozzle

OPTIONS

- ▶ 1 - Time delayed total stop
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension
- ▶ 4 - Double foam kit



Use :



Semi-pro Professional Intensive Super intensive

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		POIDS
	l/min	l/h		HP	kW	rpm	Brand	Oil	
SM 26 90	26	1560	90	5,5	4	1450	INTERPUMP	15W40	70



SAT DIMACO Constructeur, ZI, 15 rue Gustave Eiffel, 37500 CHINON (France) - Tél. + 33 (0)2 47 98 25 36

E-mail : export@dimaco.com - Site Internet : www.dimaco.com

V1 - vm