

# HOT WATER HP WASHER

Three phase - Standard use - Ref. : DIMACTION 21 200 HW



**Direct drive**  
1450 rpm

2026  
Selection



## MAIN FEATURES

- ▶ Time delayed total stop
- ▶ Easy to handle
- ▶ Lance holder



## SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : automatic shutdown of engine managed by spray gun
- Regulator : separated from the manifold
- Three phase electric engine
- Detergent application system : integrated
- Electric cord : 5 m
- Boiler : steel construction
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 24 l
- Wheels : 4 Rubber-tyred wheels
- Frame : Steel/polypropylene
- Hood : ABS



## OPTIONS

- ▶ 1 - Hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Antiscale kit (curative)
- ▶ 4 - Turbo lance



**A TOTAL STOP, WHAT IS IT?**

Standby system on the high-pressure washer

## STANDARD EQUIPMENT

- Blue hose : 10 m 3/8 double metal braided
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure

Use :



Semi-pro Professional Intensive Super intensive

## MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP			TEMPERATURE	WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil	°C	kg	cm (Lx l x h)
DIMACTION 21 200 HW	21	1260	200	10	7,5	1450	ANNOVI	15W40	65/140	160	104 x 70 x 110



SAT DIMACO Constructeur, ZI, 15 rue Gustave Eiffel, 37500 CHINON (France) - Tél. + 33 (0)2 47 98 25 36

E-mail : export@dimaco.com - Site Internet : www.dimaco.com

V1 - vm

HOT WATER