

HOT WATER HP WASHERS

Three-phase - Professional series - Réf. : FP 21 150 HW PREMIUME



Direct drive
1 450 rpm

2026
Selection



MAIN FEATURES

- ▶ Lack of fuel safety
- ▶ Lack of flame safety
- ▶ Antiscale device
- ▶ Lack of use function : stops the machine after 20 minutes of inactivity



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : automatic shutdown of engine managed by spray gun
- Regulator : Separated from the manifold
- Engine : Three phase electric engine
- Thermal circuit breaker
- Integrated detergent application system
- Detergent tank capacity : 3 l
- Electric cable : 5 m
- Boiler : stainless steel boiler, steel coil
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 35 l
- Wheels : 2 Rubber-tyred wheels and 2 castor wheels
- Frame : steel and polypropylene
- Hood : stainless steel AISI 430
- Front bumper



OPTIONS

- ▶ 1 - Hose extension
- ▶ 2 - Double foam kit
- ▶ 3 - Antiscale kit (preventive & curative)
- ▶ 4 - Turbo lance

SELECTION EQUIPMENT

- Hose reel : ABS
- Blue hose : 20 m 5/16 double metal braided
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP		TEMPÉRATURE	WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	°C	kg	cm (Lx l x h)
FP 21 150 HW PREMIUME	21	1260	150	7,5	5,6	1450	INTERPUMP	65/140	158	130 x 61 x 94

STT A TOTAL STOP, WHAT IS IT?
Standby system on the high-pressure washer

Use :

