

THREE PHASE HP WASHERS

Standard series - Ref. FP 18 160 ST



Direct drive
1450 rpm

2026
Selection



MAIN FEATURES

- ▶ High quality crankshaft pump
- ▶ Lance holders
- ▶ Wheelbarrow arms



OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension

● SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : Automatic Start/Stop system managed by the spray gun
- Regulator : separated from the manifold
- Integrated detergent application system
- Three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel frame epoxy paint
- ABS hood



A TOTAL STOP, WHAT IS IT?

Standby system on the high-pressure washer

● SELECTION EQUIPMENT

- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm single lance: with adjustable head & flat jet nozzle
- Rubber-tyred wheels : Ø 260 mm

Use :



Semi-pro Professional Intensive Super intensive

● MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP			WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	KW	rpm	Brand	Oil	kg	cm (Lx l x h)	
FP 18 160 ST	18	1100	160	7,5	5,6	1450	ANNOVI	15W40	70	140 x 62 x 77	

