

HOT WATER

The right accessory for each HP washer

			TIE		MONO	F - Stainless steel Three phase - Standard				I - Intensive three phase engine ≥ 8 HP		
Reference	Description		TIE 18 200 IGX HW	TIE 15 240 IGX HW	FP 9 120 HW	FP 21 200 HW	FP 15 200 HW	FP 14 150 HW	FP 12 160 HW	I 21 200 HW	I 21 150 HW	I 15 200 HW
● = Standard												
○ = Option												
ANTI-LIMESCALE KITS												
	KITCALC	PREVENTIVE anti-limescale kit to fix to the water inlet	●	●	○	○	○	○	○			
	KITDECALC	CURATIVE descaling kit Liquid, in a 5 l can.	○	○	○	○	○	○	○			
OPTIONS												
	EK23100ASSP	Polyphosphate cartridge	○	○	○	○	○	○	○			
	115620	Polyphosphate crystals 1 kg								○	○	○
	KITCHEMINEE	Adaptation kit for chimney pipe V1 : Ø 150 mm V2 : Ø 125 mm	V2 ○	V2 ○	V1 ○	V1 ○	V1 ○	V1 ○	V1 ○	V1 ○	V1 ○	V1 ○
	KITHORA	Hour meter	●	●								
	VST	Thermal safety valve	●	●								
HOSE REEL KIT to be mounted on HP washer (hose sold separately)												
	KITENROULPHWABS	ABS hose reel Assembly in factory only			○	○	○	○	○			
	KITENROULIHWABS	ABS hose reel Assembly in factory only								○	○	○
FLOOR CLEANERS - For use with high flow rate HP washers, minimum 900 l/h												
	LAV54	Standard 60°C max.	○	○		○	○			○	○	○
	LAV54CER	Industrial 120°C max.	○	○		○	○			○	○	○
FOAM GUNS + coupling 26000231 (M22 x 1,5)												
	CM	1 l tank 30 l/min max 200 bar max	○		○	○	○	○	○	○	○	○
	CM2H	2 l tank 21 l/min max 250 bar max	○	○	○	○	○	○	○	○	○	○
	CM5	5 l tank 21 l/min max 200 bar max	○		○	○	○	○	○	○	○	○